

HYDRAULICS

Hydraulic Test Benches For Flight Control Units SERIES >HPM-5/M-FC<



This test bench is developed to test the function of flight control units for 3000 and 5000psi systems for aircraft types like:

- AIRBUS
- ANTONOV
- BOFING
- BOMBARDIER
- EMBRAER
- FOKKER
- LOCKHEED MARTIN
- MCDONNELL DOUGLAS
- SUKHOI. etc.

- > The test bench can be supplied for Skydrol or mineral oil.
- > Several options grant an assembly of the test bench, which is in accordance with individual requirements.
- > The modular design of the unit ensures ease of transportation and service.
- > Three different types of this unit are available, other designs can be offered on request.

safety in test > safety in flight 7/17/1997

RANGE OF APPLICATION

> The Skydrol version (letter "S") can be used but is not limited to the following aircraft types:

AIRBUS A300 A319 A320	BOEING B737 B747 B757	BOMBARDIER CRJ Series	ANTONOV AN-148
A330/340 A380 A400M	B757 B767 B777 B787	EMBRAER ERJ135/145 E-Jets	SUKHOI SSJ-100

> The mineral oil version (letter "M") can be used but is not limited to the following aircraft types:

Eurofighter	Tornado	F-18	F-16	F-15	F-4	AN-124	
-------------	---------	------	------	------	-----	--------	--

3000PSI HYDRAULIC TEST BENCH

> suitable for aircraft types equipped with a 3000psi system

Туре	Flow	Flow	Flow	Flow
	HP circuit	HP circuit	LP circuit	LP circuit
	[US gpm]	[I/min]	[US gpm]	[I/min]
HPM-S/M-FC-40-30	40	151	62	235

5000PSI HYDRAULIC TEST BENCH

> suitable for aircraft types equipped with a 3000psi and 5000psi system, e.g.: A380

Туре	Flow	Flow	Flow	Flow
	HP circuit	HP circuit	LP circuit	LP circuit
	[US gpm]	[I/min]	[US gpm]	[I/min]
HPM-S/M-FC-40-50	40	151	62	235
HPM-S/M-FC-60-50	60	227	95	360

safety in test > safety in flight 7/17/19/19

OPTIONEN

> Various options can be offered to make a tailored solution to the customers requirements. e.g.: different control consoles, touch screens, etc.

TECHNICAL DATA

> Electrical connected loads (max.):

Mains connection: 3/N/PE AC 50Hz 400V

Nominal current: 32A Power: 22kVA

Mains connection: 1/N/PE AC 50Hz 230V

Nominal current: 10A / 13A Power: 2.5kVA

> Medium:

Letter "S":

Skydrol IV, Skydrol V HyJet IV, HyJet V

Letter "M":

Hydraulic oil: MIL-H-5606

MIL-H-83282 MIL-H-87257

> Dimensions:

Length: 2,795mm (9.2ft) Width: 1,982mm (6.5ft) Height: 2,500mm (8.2ft)

(Dimensions including the swivel arm)