

Passenger Door Modular Test Equipment

>MDTE1-1<



The equipment is developed to test, monitor and control the A350 passenger door test equipment and to carry out the following tests: run time, load, engineering, icing, static, emergency opening and acceptance tests.

It is possible to adapt the equipment for other aircraft types.

- > The test equipment consists of one mobile stainless steel switching cabinet.
- > The test equipment is operated by an industrial PC and the TEST-FUCHS standard software.
- > The test values are generated and processed by a Sigmatek system.
- > Connections are fitted to control the servo motors or the "Hydraulic Supply Power Unit <HVA10-350KOR>".
- > Direct DMS (data measurement system) is provided by six conductors.

GENERAL INFORMATION

- > A 19" monitor, keyboard and mouse are fitted to display and operate the software
- > The uninterruptible power supply protects the computer system in case of power failure
- > The emergency-off button ensures shutdown of the system in case of danger or emergency
- > A fan with filter dissipates excessive heat in the switch cabinet
- > A grommet is fitted for all external electrical leads, to ensure no admission of external dust and impurities

TECHNICAL DATA

> Electrical supply (requirements):

Mains supply:	3/N/PE 50/60Hz 380 to 400V
Nominal current:	6A
Power:	4kVA
Back-up fuse:	16AL
Connection:	Plug CEE 16A

> Operating conditions:

Operating temperature:	0 to 40°C (32 to 104°F)
Storage temperature:	0 to 60°C (32 to 140°F)
Altitude:	1,000m (3,280ft) above MSL
Humidity:	10 to 95% (condensing)
Noise emission:	≤85dB

> Dimensions and weight:

Width:	1,280mm	(50.4in)
Height:	1,960mm	(77.2in)
Depth:	840mm	(33.1in)
Weight:	380kg	(837.8lb)

> Measurement range:

DMS:

(20-off)	-3 to +3mV/V ±0.25% range
(4-off)	-10 to +10mV/V ±0.25% range
(6-off) (Input)	-10 to +10VDC ±0.1% range
(2-off) (Output)	-10 to +10VDC ±0.25% range
(6-off)	20°C to 90°C ±0.75% o.f.s.

Angle:

(3-off)	0 to 180deg ±0.25deg abs.
---------	---------------------------

abs. ... absolute tolerance o.f.v. ... of full scale range
 range ... measurement range



Servo controller



Control console